



Inserto ceramico Ceramic insert Inserto cerámico	COD.	 bar	 l/min	L m	l/ha								
					4 km/h	6 km/h	8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h	20 km/h
✓	BX010	2	3.2	2.1	227	152	114	91	76	65	57	51	45
		3	3.9	2.6	225	150	113	90	75	64	56	50	45
		4	4.5	3.1	218	145	109	87	73	62	54	48	44
		5	5.0	3.9	194	129	97	77	65	55	48	43	39
		6	5.5	4.4	188	125	94	75	63	54	47	42	38
✓	BX020	2	6.5	2.8	346	230	173	138	115	99	86	77	69
		3	7.9	3.2	370	247	185	148	123	106	93	82	74
		4	9.1	3.5	391	261	195	156	130	112	98	87	78
		5	10.2	3.7	413	276	207	165	138	118	103	92	83
		6	11.2	4.0	419	279	209	168	140	120	105	93	84
✓	BX025	2	7.7	2.5	461	307	230	184	154	132	115	102	92
		3	9.4	3.0	470	313	235	188	157	134	118	104	94
		4	10.9	3.3	493	329	247	197	164	141	123	110	99
		5	12.1	3.5	520	347	260	208	173	149	130	116	104
		6	13.3	3.6	554	369	277	222	185	158	138	123	111
✓	BX045	2	14.1	2.9	731	487	365	292	244	209	183	162	146
		3	17.3	3.0	865	577	433	346	288	247	216	192	173
		4	20.0	3.3	908	605	454	363	303	259	227	202	182
		5	22.3	3.5	957	638	479	383	319	273	239	213	191
		6	24.5	3.6	1019	680	510	408	340	291	255	227	204
✗	BX060	2	18.1	3.0	906	604	453	363	302	259	227	201	181
		3	22.2	3.4	979	653	490	392	326	280	245	218	196
		4	25.6	4.0	961	641	481	385	320	275	240	214	192
		5	28.7	4.4	977	651	489	391	326	279	244	217	195
		6	31.4	4.7	1002	668	501	401	334	286	250	223	200
✗	BX080	2	25.3	3.5	1085	723	542	434	362	310	271	241	217
		3	31.0	4.0	1163	775	581	465	388	332	291	258	233
		4	35.8	4.0	1342	895	671	537	447	384	336	298	268
		5	40.0	4.1	1464	976	732	586	488	418	366	325	293
		6	43.8	4.1	1604	1069	802	642	535	458	401	356	321

Manicotto filettato attacco rapido per barra
Boom quick-fitting threaded adapter
Terminal roscado para barra



COD.	F	PACK
400 277	G1/2 (BSP)	25
400 278	G3/4 (BSP)	25



COD.	PACK
402 909 xx	25

Portagetto di fine barra per ugelli BX
Boom-end nozzle holder for BX nozzles
Porta-boquilla de final de barra para boquillas BX



COD.
(Viton®)
4065 845C

1/2"



Portagetto per alimentazione barra
Nozzle holder for boom feeding
Porta-boquillas para alimentación barra



COD.
400 64B

I raccordi con attacco femmina 1/2"
cod. 100215 e 100219 sono da ordinare separatamente

Fittings with 1/2" female connector
code 100215 and 100219 must be ordered separately

Los empalmes con acople hembra 1/2"
cód. 100215 y 100219 se deben ordenar por separado