




COD.	 bar	 drop	 l/min	I/ha (spazio tra gli ugelli: 50 cm) I/ha (nozzle spacing: 50 cm) I/ha (espacio entre las boquillas: 50 cm)							
				6 km/h	8 km/h	10 km/h	12 km/h	14 km/h	16 km/h	18 km/h	20 km/h
TFS11002	2	F	0.65	130	98	78	65	56	49	43	39
	3	VF	0.80	160	120	96	80	69	60	53	48
	4	VF	0.92	184	138	110	92	79	69	61	55
	5	VF	1.03	206	155	124	103	88	77	69	62
TFS11003	2	F	0.98	196	147	118	98	84	74	65	59
	3	F	1.20	240	180	144	120	103	90	80	72
	4	F	1.39	278	209	167	139	119	104	93	83
	5	F	1.55	310	233	186	155	133	116	103	93
TFS11004	2	F	1.31	262	197	157	131	112	98	87	78
	3	F	1.60	320	240	192	160	137	120	107	96
	4	F	1.85	370	278	222	185	159	139	123	111
	5	F	2.07	414	311	248	207	177	155	138	124
TFS11005	2	F	1.63	326	244	196	163	140	122	109	98
	3	F	2.00	400	300	240	200	171	150	133	120
	4	F	2.31	462	346	277	231	198	173	154	139
	5	F	2.58	516	387	310	258	221	193	172	155

	DIMENSIONE DELLE GOCCE DROP SIZE RATING DIMENSIONES DE LAS GOTAS	
VF	Molto fine-Very fine-Muy fina	< 119µm
F	Fine-Fine-Fina	119µm ÷ 216µm

millesimo di millimetro (Es.: 250µm = 0.25 mm)
µm= thousandth of millimeter (E.g.: 250µm = 0.25 mm)
milésimo de milímetro (Ej.: 250µm = 0.25 mm)

